

General Data	
Max. distance sockets	20 m
Max. # of simultaneous users	1
Estimated cleaning surface	200 m ²
Estimated # of sockets	7

Vacuum unit specifications	
Primary filter	Cyclonic filtration
Secondary filter	Textile filter (2 possibilities)
Capacity	18 L
Unit dimensions (W x H x D)	0,38 x 1,00 x 0,40
Required mounting space	0,75 x 1,40 x 0,75



Motor specifications	
General	220 - 250 VAC, 50 Hz Insulation class E
Nom. power	1200 W
Max. power	1560 W
Max. current	6,0 A
Max. revolutions	22000 / min
Fuse rating	8 A
Motorframe	145 mm
Carbon brushes	Ref. EF
Motor control	12 VDC signal with safety transformer (VDEO551 - relay 16A)

Turbine specifications	
Motor Type	By-Pass Exterior 50mm outlet
Number of stages	3
Max. Negative Pressure	2733 mm H ₂ O
Max. Airflow	48,1 L/sec
Max. AirWatts	380 W

Availability	
1.0040.1411	Central vacuum unit MI 1411 - PC/ABS - Normal textile filter
1.0050.1411	Central vacuum unit MI 1411 - PC/ABS - Self-cleaning textile filter
1.0056.1411	Central vacuum unit MI 1411 - PC/ABS - COMFORT Edition

Certification	
EMC KEMA CE	Electromagnetic Compatibility KEMA-KEUR & KEYMARK Approved



IMPORTANT NOTE Technical data is subject to change without notice. Please check our website for latest information.

ELEK TRENDS PRODUCTIONS sa/nv

Rue des Bengalis 4 - B-7700 Moeskroen - Belgium - T: +32 (0)56/ 48 15 90 - F: +32 (0)56/ 48 15 91 - info@elek-trends.be
www.elek-trends.be