

General Data	
Max. distance sockets	50 m
Max. # of simultaneous users	1
Estimated cleaning surface	700 m ²
Estimated # of sockets	15

Vacuum unit specifications	
Primary filter	Cyclonic filtration
Secondary filter	Textile filter (2 possibilities)
Capacity	18 L
Unit dimensions (W x H x D)	0,38 x 1,00 x 0,40
Required mounting space	0,75 x 1,40 x 0,75



Motor specifications	
General	220 - 250 VAC, 50 Hz Insulation class E
Nom. power	1750 W
Max. power	1850 W
Max. current	8,5 A
Max. revolutions	28086 / min
Fuse rating	10 A
Motorframe	145 mm
Carbon brushes	Ref. U 3690/3
Motor control	12 VDC signal with safety transformer (VDE0551 - relay 16A)

Turbine specifications	
Motor Type	By-Pass Exterior 50mm outlet
Number of stages	3
Max. Negative Pressure	3651 mm H ₂ O
Max. Airflow	52,7 L/sec
Max. AirWatts	627 W

Availability	
1.0040.2411	Central vacuum unit MI 2411 - PC/ABS - Normal textile filter
1.0050.2411	Central vacuum unit MI 2411 - PC/ABS - Self-cleaning textile filter
1.0056.2411	Central vacuum unit MI 2411 - PC/ABS - COMFORT edition

Certification	
EMC KEMA CE	Electromagnetic Compatibility KEMA-KEUR & KEYMARK Approved



IMPORTANT NOTE Technical data is subject to change without notice. Please check our website for latest information.

ELEK TRENDS PRODUCTIONS sa/nv

Rue des Bengalis 4 - B-7700 Moeskroen - Belgium - T: +32 (0)56/ 48 15 90 - F: +32 (0)56/ 48 15 91 - info@elek-trends.be
www.elek-trends.be