

MI 1511



GENERAL DATA

Max. distance motor to the furthest socket.....	35 m
Max. number of simultaneous users	1
Estimated cleaning surface	300 m ²
Estimated sockets.....	10

UNIT SPECIFICATIONS

Primary filtration	Cyclonic or paper bag
Secondary filtration	Textile filter*
Capacity dust container	18 L
Dimensions (W x H x D)	0,38 x 1,00 x 0,40
Installed dimensions	0,75 x 1,40 x 0,75

MOTOR SPECIFICATIONS

General	220 - 250 VAC, 50 Hz
Power (nom.)	1200 W
Power (max.)	1536 W
Max. current	7,0 A
Revolutions (max.)	25790 / min
Fuse rating	8 A
Motorframe	145 mm
Carbon brushes.....	Ref. I.0710.3423
Motor control	12VDC signal with safety transformer (VDE0551 - relay 16A)

TURBINE SPECIFICATIONS

Motor Type	Bypass
Number of stages	3
Negative pressure	3482 mm H ₂ O
Max. Airflow	44,7 L/sec
AirWatts	448 W

AVAILABILITY

I.0040.1511	Central vacuum unit MI 1511 - PC/ABS
I.0044.1511	Central vacuum unit MI 1511 - PC/ABS - isolated
I.0051.1511	Central vacuum unit MI 1511 - PC/ABS - acoustic

CERTIFICATION

EMC	Electromagnetic Compatibility
CE	Conforms

* Textile filter not included in version with paper bag

Technical data is subject to change without notice.
Please check our website for latest information.